

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2018368-4
Report Reference E210608-20031121
Date 24-Jan-2023

Issued to: Hans Turck GmbH & Co. KG
Witzlebenstrasse 7
Muelheim an der Ruhr 45472
Germany

This is to certify that representative samples of NRKH - Proximity Switches
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL508, Industrial Control Equipment

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2018368-4
Report Reference E210608-20031121
Date 24-Jan-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
Cat. Nos. B or N,, followed by C or CF, may be followed by E, followed by a 1 or 2 digit number, followed by M, K, KT, P, PT, S, S185, Q or CP, followed by a 1 or 2 digit number, may be followed by SR, followed by A, R or V, followed by N or P, followed by 4, may be followed by X, may be followed by 2, may be followed by -Xm where X = number representing cable length in meters. May be followed by /S or /CS followed by 2 to 5 digits.	Proximity switches
Cat. Nos. B or N, followed by C or CF,, may be followed by E, followed by a 1 or 2 digit number, followed by M, K, KT, P, PT, S, S185, Q or CP, followed by a 1 or 2 digit number, may be followed by SR, followed by A, R or V, followed by N or P, followed by 4, may be followed by X, may be followed by 2, may be followed by -H1, B1, B2, B3, V1, followed by 1, 3 or 4, followed by 3, 4 or 5, may be followed by a two digit number. May be followed by /S or /CS followed by 2 to 5 digits.	Proximity switches

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>