TP-306A-CF-H1141-L1000
Temperature Detection – Probe



Features

- Max. temperature connector: 120°C
- Connection mode: 4-wire connection

Wiring diagram



Technical data

Type	TP-306A-CF-H1141-L1000
ID	9910479
Temperature range	
Measuring range	-50…105 °C
	-58…221 °F
Accuracy	±0.15 K + 0.002 • |t| (-30…300 °C)
Self-heating	0.4 K/mW at 0 °C
Measuring element	Pt100, DIN EN 60751, class A; connection mode: 4-wire connection
Response time	t 0.5 = 8 s / t 0.9 = 20 s in water at 0.2 m/s
Immersion depth L	1000 mm
Outer diameter	6 mm
Length sleeve (l)	50 mm
Protection class	IP67
Mechanical data	
Housing material	Stainless steel, 1.4404 (AISI 316L)
Sensor material	Stainless steel, 1.4404 (AISI 316L)
Process connection	For compression fittings, for direct mounting
Electrical connection	Connector, M12 × 1
Cable quality	AWG24, PP + TPE
Core cross-section	4 mm^2
Reference conditions acc. to IEC 61298-1	
Temperature	15…+25 °C
Atmospheric pressure	860…1060 hPa abs.
Humidity	45…75 % rel.

Functional principle

Resistance thermometers are used for the detection and monitoring of temperatures to optimize and control a process.
Typical applications are in machine and plant construction as well as in the process industry.
The core element of the temperature probe is a temperature-dependent resistor.

TP-306A-CF-H1141-L1000| 27-03-2025 12-19 | Technical modifications reserved

Technical data

Auxiliary power	24 VDC
Tests/approvals	
Approvals	cULus
UL registration number	E345414
MTTF	2283 years acc. to SN 29500 (Ed. 99) 20 °C

Accessories

Dimension drawing	Type	ID	
	WKC4.4T-2/TEL	6625025	Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval
	RKC4.4T-2/TEL	6625013	Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval
	RKC4.4T-2/TXL	6625503	Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PUR, black; cULus approval
	WKC4.4T-2/TXL	6625515	Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PUR, black; cULus approval

TP-306A-CF-H1141-L1000| 27-03-2025 12-19 | Technical modifications reserved